

SDS prepared by Steve Davis of Aardvark Clay & Supplies

GHS - United States

### Section 1. Product and Company Identification

Product Name Raku Glaze - RG-315 - X-MAS Foil

**Synonym** Ceramic Glaze - dry

**Supplier/** Aardvark Clay & Supplies **Manufacturer** 1400 East Pomona St.

Santa Ana, Ca. 92705 USA 714-541-4157 phone 714-541-2021 fax contact@aardvarkclay.com

**Emergency Phone Number** 911

Product Use Pottery Manufacturing

**Restrictions on use** Not applicable

### Section 2. Hazards Identification

GHS/Hazcom 2012 Labels	GHS/Hazcom 2012 Classifications:		
	Health:		
	REPRODUCTIVE TO	XICITY - Category 2 (borax)	
	ACUTE TOXICITY (C	ral) - Category 4 (copper carbonate)	
	EYE IRRITANT -	Category 2A (borax)	
Signal Word:	Environmental:	Not Hazardous	
Warning	Physical:	Not Hazardous	

Hazard Statements:				
Health:				
H302	Harmful if swallowed.	H319	Causes serious eye irritation	
H372	Causes damage to organs (lungs) through prolonged or	H360	H360 May damage fertility or the unborn child.	
	repeated exposure (inhalation).			
Environmental:		Physic	Physical:	
Not hazardous Not hazardous		zardous		

Not na	zardous		Not nazardous		
Precau	ition Statements:				
Prevei	ntion				
P262	Do not get into eyes, on skin, or on cl	othing.	P284	[In case of inadequate ventilation] wear respiratory protection.	
P264	Wash hands thoroughly after handlin	g.	P261	Avoid breathing dust/spray.	
P272	Contaminated clothing should not be workplace.	allowed out of the	P263	Avoid contact during pregnancy/while nursing.	
P280	Wear protective gloves/ protective cl face protection.	othing/ eye protection/	P202	Do not handle until all safety precautions have been read and understood.	
			P270	Do not eat, drink, or smoke when using this product.	
Respo	nse				
P314	Get medical advice/attention if you for	eel unwell.	P391	Collect Spillage.	
P305+	IF IN EYES: Rinse cautiously with water for several minutes.		P304+	IF INHALED: Remove person to fresh air and keep comfortable	
P351+	Remove contact lenses if present and easy to do – continue		P340	for breathing.	
P338	rinsing.				
P337+	If eye irritation persists, get medical advice/attention.		P301+	IF SWALLOWED: Call a POISON CENTER or doctor/physician if	
P313			P312+	you feel unwell. Rinse mouth.	
			P330		
P302+	IF ON SKIN: Wash with plenty of soap	and water.	P363	Wash contaminated clothing before reuse.	
P352					
P332+	If skin irritation occurs: Get medical advice/attention.				
P313					
Storag	Storage		Dispos	al	
P402	Store in a dry place.		P501	Dispose of contents/container in accordance with	
P404	Store in a closed container.	·		local/regional/national/international regulations.	
Hazard	ds not otherwise classified:	ippery when wet.	% of ir	gredients with unknown acute toxicity: None known.	



SDS prepared by Steve Davis of Aardvark Clay & Supplies

GHS - United States

## Section 3. Composition / Information on Ingredients

### Substance/Mixture:

Mixture - A trade secret claim is made for this glaze.

Chemical	CAS Numbers	Ingredien	ts	Chemical % of Mixture	
Sodium-Calcium Pentaborate Octahydrate		CAS # 1319-33-1	Ulexite	from Gerstley Borate	<10
Nac	D.2CaO.5B2O3.5H2O				
Di-Calcium Hexaborate Pentahydrate	Ca2B6O11.5H2O	CAS # 12291-65-5	Colemanite	from Gerstley Borate	<25
Disodium Tetraborate Pentahydrate	Na <sub>2</sub> B4O <sub>7</sub> .5H <sub>2</sub> O	CAS # 12179-04-3	Borax		Trade Secret Claim
Kaolinite	Al2O3.2SiO2.2H2O	CAS # 1332-58-7	Kaolin		Trade Secret Claim
Cupric Carbonate	CuCO3	CAS # 12069-69-1	Copper Car	bonate	Trade Secret Claim

## Section 4. First-Aid Measures

Description of first-aid Measures:				
First-aid measures general	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical attention.			
First-aid measures after inhalation	Move victim to well ventilated area. If mechanical discomfort persists, seek medical attention.			
First-aid measures after skin contact	Remove contaminated clothing. Wash affected area with soap and warm water.  Obtain medical attention if irritation persists.			
First-aid measures after eye contact	Rinse cautiously with water for 30 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking, or redness persists.			
First-aid measures after ingestion	Rinse mouth. Do NOT induce vomiting. Small amount unlikely to be toxic by ingestion. If large amount ingested or if discomfort persist, drink two glasses of water and seek medical attention.			
Most Important Symptoms and Effects, both Acute and Delayed:				
Symptoms/injuries	Causes damage to organs through prolonged or repeated exposure (inhalation) from dust.			
Symptoms/injuries after inhalation	May cause cancer by inhalation. Dust from this product may cause irritation to the respiratory tract.			
Symptoms/injuries after skin contact	Prolonged contact with large amounts of dust may cause mechanical irritation.			
Symptoms/injuries after eye contact	Contact with large amounts of dust may cause mechanical irritation, pain, blinking, or redness.			
Symptoms/injuries after ingestion	If a large quantity has been ingested, symptoms may include nausea, vomiting, and diarrhea.			
Chronic symptoms	Causes damage to organs through prolonged or repeated exposure (inhalation) from dust.			

If exposed or concerned, get medical advice and attention.

### Section 5. Fire-Fighting Measures



#### National Fire Protection Association (U.S.A.)

Suitable extinguishing media	This product is not combustible.
	Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	No restrictions on extinguishing media for this mixture.
Special hazards arising from the substance or mixture	This mixture is not flammable and does not support fire.
Hazardous thermal decomposition products	This mixture does not contain hazardous decomposition products.
Special protective actions for fire-fighters	None known.
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment.

## Section 6. Accidental Release Measures

Use of personal precautions	Avoid inhalation of dust.
	Wear a N-95 face mask when cleaning up dust.
Emergency procedures	There are no emergency procedures required for this mixture.
Methods and Materials for containment	There are no special spill measures that apply for this mixture.
Clean up procedures	For dusts, use a vacuum to clean up spillage. If appropriate, use gentle water spray to wet
	down and minimize dust generation. Place dust in a sealed container.
	Wear a N-95 face mask when cleaning up dust.

## Section 7. Handling & Storage

Precautions for safe handling	Keep bags out of direct sunlight. Do not expose this mixture to moisture until use.
	Do not expose liquid glaze to freezing.
	Use proper lifting techniques to avoid physical injury.
Recommendations on the conditions for safe storage	No special storage considerations, but keep in a dry, cool location.



SDS prepared by Steve Davis of Aardvark Clay & Supplies

GHS - United States

Section 8. Exposure Controls / Personal Protection				
Chemical Name	CAS Numbers	Occupational Exposure Limits		
Sodium-Calcium Pentaborate Octahydrate	CAS # 1319-33-1	ACGIH TLV: TWA 2 mg/ m <sup>3</sup>		
NaO.2CaO.5B2O3.5H2O		OSHA PEL: TWA 5 mg/m <sup>3</sup> (respirable)		
		OSHA PEL: TWA 15 mg/m <sup>3</sup> (total)		
		CAL OSHA PEL: TWA 5 mg/ m <sup>3</sup>		
Di-Calcium Hexaborate Pentahydrate	CAS # 12291-65-5	ACGIH TLV: TWA 2 mg/ m <sup>3</sup>		
Ca2B6O11.5H2O		OSHA PEL: TWA 5 mg/m³ (respirable)		
		OSHA PEL: TWA 15 mg/m³ (total)		
		CAL OSHA PEL: TWA 5 mg/ m <sup>3</sup>		
Disodium Tetraborate Pentahydrate	CAS # 12179-04-3	ACGIH TLV: TWA 2 mg/ m <sup>3</sup>		
Na <sub>2</sub> B4O <sub>7</sub> .5H <sub>2</sub> O		OSHA PEL: TWA 5 mg/m³ (respirable)		
		OSHA PEL: TWA 15 mg/m³ (total)		
		CAL OSHA PEL: TWA 5 mg/ m <sup>3</sup>		
Kaolinite	CAS#1332-58-7	ACGIH TLV: TWA 2 mg/ m³ (respirable) / particulate matter containing no		
Al2O3.2SiO2.2H2O		asbestos and <1% crystalline silica (respirable)		
		OSHA PEL: TWA 5 mg/m³ (respirable)		
		OSHA PEL: TWA 15 mg/m³ (total)		
		CAL OSHA PEL: TWA 2 mg/ m³ (respirable)		
Cupric Carbonate	CAS # 12069-69-1	ACGIH TLV: TWA not established		
CuCO3		OSHA PEL: TWA not established		
No Occupational Exposure Limits are listed		OSHA PEL: TWA not established		
for this chemical.		CAL OSHA PEL: TWA not established		

**Appropriate engineering controls:** When mixing this mixture, use local exhaust ventilation or other engineering controls as required to maintain exposures below applicable occupational exposure limits (TLV).

### Recommendations for personal protective measures

**Local Exhaust:** When mixing glazes, use sufficient local exhaust to reduce the level of respirable dust to the applicable standards set forth in Section III - ACGIH "Industrial Ventilation, A Manual of Recommended Practice," latest edition.

Respiratory Protection: Dust is generated when working with this mixture. To minimize exposure to dust and/or quartz, the mixing of this mixture should be conducted with sufficient ventilation. Respirable dust and quartz levels should be monitored regularly. Dust and quartz levels in excess of appropriate exposure limits should be reduced by feasible engineering controls, including (but not limited to) wet suppression, ventilation, and process enclosure. When such controls are not feasible, NIOSH/MSHA approved respirators must be worn in accordance with a respiratory protection program which meets OSHA requirements as set forth at 29 CFR1910.134 and ANSI Z88.2-1080 – "Practices for Respiratory Protection".

In most cases, a disposable N-95 Particulate Respirator is sufficient.

**Eye Protection:** Use NIOSH/OSHA approved safety glasses with side shields. Face shields can also be used when mixing dry glaze. Wear tight fitting dust goggles when excessively (visible) dusty conditions are present or are anticipated. NIOSH recommends that contact lenses not be worn when working with crystalline silica dust.

Skin Protection: Use gloves and/or protective clothing if abrasion or allergic reactions are experienced.

 $\label{prop:work-Hygienic Practices:} \textbf{Avoid creating and breathing dust.}$ 

Wear NIOSH/MSHA approved dust mask when working in dusty conditions - (N-95).

Food, beverages, and smoking materials should NOT be in the work area.

Persons using ceramic materials should wash hands thoroughly before eating, drinking, smoking, or applying cosmetics.



**Protective Clothing Pictograms** 

N-95 face mask



SDS prepared by Steve Davis of Aardvark Clay & Supplies

GHS - United States

# Section 9. Physical & Chemical Properties

Physical State	Powder
Appearance	Tinted powder
Odor	None
Odor Threshold	Not Applicable
рН	6-8
Solubility in Water	None
Melting Point	1050 °C (1900°F)
Freezing Point	<0 °C (<32°F)
Specific Gravity / Relative Density	2.35 g/cc
Evaporation Rate	No data available
Flash Point	Not Applicable
Auto-Ignition Temperature	Not Applicable
Decomposition Temperature	Not Applicable
Flammability	Not Applicable
Vapor Pressure	Not Applicable
Vapor Density	Not Applicable
Explosive Limits	Not Applicable
Viscosity	Not Applicable
Partition Coefficient: n-octanol/water	Not Applicable
Initial Boiling Point & Boiling Range	Not Applicable

## Section 10. Stability & Reactivity

Reactivity	Hazardous reactions will not occur under normal conditions.
Chemical stability Stable at standard temperature and pressure.	
	No stabilizers required to maintain chemical stability.
Possibility of hazardous reactions	Hazardous polymerization will not occur.
Conditions to avoid	None known
Incompatible materials	None known
Hazardous decomposition products	None known

### Section 11. Toxicological Information

Routes of Exposure: Inhalation of dry glaze dust, Ingestion

Routes of Exposure.	initial action of all y g	laze dust, ingestion	
Descriptions of the delayed, immediate, or chronic effects from short- and long-term exposure			
Inhalation	Inhalation of high	concentrations of dry glaze dust may cause mechanical irritation and discomfort.	
Eye Contact	May cause serious	eye irritation.	
Skin Contact/Irritation	Not a primary skin	irritant. May cause dry skin.	
Sensitization	Not a sensitizer.		
Ingestion	If a large quantity has been ingested, symptoms may include nausea, vomiting, and diarrhea.		
Chronic Effects			
OSHA Carcinogen	None Known		
Mutagenic Effects	None Known		
Teratogenic Effects	None Known		
<b>Developmental Toxicity</b>	None Known		
Description of symptoms		None Known	
Numerical Measures of toxicity		None Known	

Chemicals with Carcinogen Potential	CAS#	OSHA	IARC	NTP
None	-	None	None	none

# Section 12. Ecological Information (non-mandatory)

Ecotoxicity	None Known
Biochemical oxygen demand (BOD5)	None Known
Chemical oxygen demand(COD)	None Known
Products of Biodegradation	None Known
Toxicity of the products of Biodegradation	None Known
Bioaccumulation Potential	None Known
Potential to move from soil to groundwater	None Known
Other adverse effects	None Known



SDS prepared by Steve Davis of Aardvark Clay & Supplies

GHS - United States

### Section 13. Disposal Considerations

Personal Protection	Refer to Section 8: "Recommendations for Personal Protective Measures" when disposing of glaze waste.		
Appropriate disposal containers	Standard waste disposal containers – no specials requirements.		
Appropriate disposal methods	Disposal of this mixture should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. In most cases, this is normal waste disposal. The generation of waste should be avoided or minimized. Dispose of non-recyclable products via a licensed waste disposal contractor. Waste packaging should be recycled. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains, and sewers.		
Physical and chemical properties	Waste should be placed in a sealed container or in a manner that reduces or eliminates the release of the product.		
that may affect disposal	Packaging should be recycled before disposal.		
Sewage disposal	Do not dispose of into sinks or toilets. They will clog. Never dispose of this product into a sewer system.		
Special precautions for landfills	There are no special precautions for disposal in a landfill.		
or incineration activities	This product is non-combustible and is not suitable for incineration.		

### Section 14. Transportation Information

Regulatory Information	UN Number	UN Proper Shipping Name	Transport Hazard Class	Packing Group Number	Bulk Transport Guidance	Special Precautions
DOT Classification	Not regulated	-	-	-	-	-
TDG Classification	Not regulated	-	-	-	-	-
ADR/RID Class	Not regulated	-	-	-	-	-
IMDG Class	Not regulated	-	-	-	-	-
IATA-DGR Class	Not regulated	-	-	-	-	-

# Section 15. Regulatory Information

TSCA – Toxic Substances Control Act - EPA	Quartz and other chemicals are listed in the TSCA Chemical Substance Inventory	
California Prop. 65	This mixture contains no chemicals listed on the	
	Proposition 65 list of carcinogens or reproductive toxicants.	
SARA/Title III	This mixture contains no substances at or above the	
(Emergency Planning & Community Right-to-Know Act)	reporting threshold under Section 313, based on available data.	

### Section 16. Other Information

### **Definitions**

**OSHA** means Occupational Safety & Health Administration

IARC means International Agency for Research on Cancer

NTP means National Toxicology Program

**CAS** means Chemical Abstract Service

**ACGIH** means American Conference of Governmental Industrial Hygienists

**CAL-OSHA** means California OSHA, most CAL-OSHA standards defer to the federal OSHA standards

**OSHA** means Occupational Safety & Health Administration

**OSHA PEL** means OSHA Permissible Exposure Limit

TWA means Time Weighted Average (average exposure on the basis of an 8h/day, 40h/week work schedule)

TLV means Threshold Limit Value - American Conference of Governmental Industrial Hygienists (ACGIH)

This SDS is in compliance with The Globally Harmonized System of Classification and Labeling of Chemicals (GHS) – prepared Oct. 23, 2015. This data sheet is subject to change without notice.

Information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Nothing herein is to be construed as recommending any practice or any product in violation of any patent or in violation of any law or regulation. It is the user's responsibility to determine for himself the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. We make no warranty as to the results to be obtained in using any material and, since conditions of use are not under our control, we must necessarily disclaim all liability with respect to the use of any material supplied by us.